Elite *TB 872*

Utopia Be® tweeter




- Pure Beryllium inverted dome
- High power Neodymium ring magnet
- Thick cast zinc alloy mounting

SPECIFICATIONS

Nominal power	20W
Maximum power	200 W
Sensitivity	94.1 dB
Cone	Beryllium
Surround	Poron®
Nom. impedance	8Ohm
DC resistance	6Ohm
VC diameter	20 mm
VC height	1.4mm
Former	Aluminum
Layers	2
Wire	Aluminum
Inductance	-
Xmax	-
Magnet dxh	Neodymium
Magnet weight	-
Flux density	2.1 T
Gap height	2.5 mm
Net weight	-

FREQUENCY RESPONSE / IMPEDANCE




PARAMETERS

Fs	1294 Hz
Vas	-
Qts	-
Qes	-
Qms	-
Re	6Ohm
Sd	7.07cm²
Cas	-
Mas	-
Ras	-
Cms	-
Mms	-
Rms	-
Ces	-
Les	-
Res	-
Bl	-
SPL	93 dB/W/m

MECHANICAL DRAWING

Unit: mm



©Focal-JMlab - SCOS-041108/4

FOCAL the Spirit of Sound

UTOPIA BE
Ultima

TWULTIMA




- IAL 2 Technology
- Grande Utopia III tweeter

SPECIFICATIONS

Nominal power	50W (with filtering)	
Maximum power	200W (with filtering)	
Sensitivity (2,83V/1m)	93dB	
Cone	Be	
Surround	Poron	
Nom. impedance	6Ω	
DC resistance	5.8Ω	
VC diameter	20 mm	$0^{13/16}$"
VC height	1.4 mm	$0^{1/16}$"
Former	Aluminium	
Layers	2	
Wire	Copper	
Inductance	-	
Xmax	± 0.1mm	
Magnet d x h	38 mm x 35 mm	$1^{1/2}$" x $1^{3/8}$"
Magnet weight	190 g	0.42lbs
Flux density	-	
Gap height	1.5 mm	$0^{1/16}$"
Net weight	300 g	0.66lbs


FREQUENCY RESPONSE/IMPEDANCE




PARAMETERS

Fs	535Hz
Vas	0.03 liters
Qts	0.37
Qes	0.5
Qms	1.4
Re	5.8Ω
Sd	8 cm^2
Cas	2.38E-08m^5/N
Mas	84.1kg/m^4
Ras	892582Ω.ac
Cms	367µm/N
Mms	0.24 g
Rms	0.57 kg/s
Ces	25.6mF
Les	3.44mH
Res	16.24Ω
BI	3.06N/A
SPL	92dB/W/m

MECHANICAL DRAWING





Elite
"HAUTE COUTURE" SOUND

FOCAL®
THE SPIRIT OF SOUND

Focal® is a trademark of Focal-JMlab®-Tel. (33) 04 77 43 57 00 - www.focal.com - Images may not conform exactly to specific product. Photos L'Atelier Sylvain Madelon - SCFG-140324/1