



Search all articles:



Produ

STAGE EQUIPMENT

[Stage Link](#) |
 [Home](#) |
 [News](#) |
 [Download](#) |
 [Tech Support](#) |
 [Service/repair](#) |
 [Where to Buy](#) |
 [Contact](#)



[Print this page](#)

[Master](#) > [Bulk Cables](#) > [Loudspeaker](#)

HPC644 (Bulk cables)

Flexible 4-conductor twisted speaker cable.

Order code : HPC644

Image :



Datasheet

Application fields : Audio connections

Conductors : Bare copper
14 AWG = 53x0.30 mm (4.00 mm²)

Insulation : PVC ø 4.20 mm

Jacket : Flexible PVC 60 shore ø 13.20 mm

Conductor resistance : 4.5 Ohm/Km @ 20°C

Conductor/conductor capacitance : 120 pF/mt @ 1 KHz

Operating temperature : -20°C / +70°C

Working voltage : 300 / 500 V

Weight : 344.80 Kg/Km

Minumum bendig radius : 10x overall diameter

Colours Available : Black

Technical notes : 100 mt. carton reel
Construction&Controls: complying with CEI 20-20 regulations



Legal Notices and Terms of Use | Privacy Statement
Proel S.p.A. (World Headquarters - Factory) Via alla Ruenia 37/43 - 64027 Sant'Omero (TE)
Website feedback: webmaster@proelgroup.com